S7100
MATTING ADDITIVE

DESCRIPTION:
S7100 Matting Additive which can be used in S5000 HS Top Clear.

FEATURES:

- **FOR REPAIRING MATT AND SEMI-MATT FINISHES**
- **ONLY FOR UNDERHOOD AND ADD ON PARTS**
- **CAN BE USED IN SYROX S5000 HS TOP CLEAR**

PRODUCTS:

- S7100 MATTING ADDITIVE

- S5000 HS TOP CLEAR

- S6000 HS ACTIVATOR SLOW

- S6010 HS ACTIVATOR STANDARD

- S6020 HS ACTIVATOR FAST

SYROX REFINISH SYSTEM

CLEARCOAT:
- S5000 HS TOP CLEAR
- S5100 AIR DRY CLEAR SCRATCH RESISTANT

BASECOAT:
- S100-S940 WATERBORNE BASECOAT

UNDERCOATS:
- S1000 UNIVERSAL POLYESTER PUTTY
- S3020 SANDING SURFACER LIGHT GREY
- S3060 SANDING SURFACER DARK GREY
- S2000 1K WASH PRIMER
- S2500 PLASTIC ADHESION PROMOTOR

For professional use only!

TECHNICAL DATA SHEET

S7100
MATTING ADDITIVE



PRODUCT PREPARATION

Mixing recommendation for S5000 HS TOP CLEAR

All mixing weights are: Clear / Additive

MATT

Weight (g): 270 / 730

SEMI-MATT

By weight (g): 330 / 670

SATIN GLOSS

By weight (g): 380 / 620



PRODUCT MIX

By volume 3:1
All Syrox Activators except S6030

30 - 60 min / 20°C

APPLICATION

Refer to the Syrox S5000 HS TOP CLEAR TDS

STIRRING

Thorough stirring of S7100 Matting Additive is required before mixing with S5000. Ensure all components are well stirred when making ready for use.

TECHNICAL REMARKS

- The use of different activators, methods of application, drying conditions and film thicknesses leads to different gloss levels (up to 20%)
- S7100 Matting Additive will extend normal drying times

SAFETY

- This product is classified according to regulation (EC) 1272/2008 (CLP).
- It is strongly recommended to use appropriate personal protection equipment during application.
- Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the paint system build-up are from Syrox®. System properties will not be valid when the related material is used in combination with any other materials or additives not belonging to Syrox®, unless explicitly indicated otherwise.

AN AXALTA COATING SYSTEMS BRAND

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved.

2/2 EN S7000-0 09-2016
This technical data sheet supersedes all previous issues